

## AQUOS BOARD<sup>®</sup> Interactive Display The Smart Alternative for Interactive Education



## Classes are conducted the way you want

- The equipment is familiar and intuitive. And it's maintenance-free. No bulbs to replace, no shadows and no warm up/ power down time.
- Classroom lessons are more productive because there is no need to learn an entirely new system.
- Take advantage of inking functionality in Microsoft<sup>®</sup> Office applications and Microsoft Edge Internet browser. For example, you can directly annotate and save within PowerPoint<sup>®</sup> without having to use or purchase a third party overlay or application.



### Open architecture yields seamless integration

- Seamlessly integrates with and leverages your existing classroom infrastructure and software investments.
- Integrates with leading learning management systems such as Blackboard<sup>®</sup>, Promethean<sup>®</sup> ActivInspire and ClassFlow<sup>™</sup>, Google<sup>®</sup> Classroom, Splashtop<sup>®</sup> Classroom and more.
- Works great with your existing AV control systems so you can take collaboration to the next level.



### Increased student engagement and teacher mobility

- Helps create an immersive and collaborative environment for students and teachers alike.
- Helps enable a personalized, 1:1 learning environment by wirelessly communicating with mobile devices using Sharp Touch Display Link or third party applications including Mirroring360 by Splashtop<sup>®</sup>.
- You have the freedom to save and share classroom lesson plans, annotations and lectures.

### To view more information, visit business.sharpusa.com/AQUOS-BOARD

©2020 Sharp Electronics Corporation. All rights reserved. Design and specifications subject to change without notice. Sharp, Sharp Pen Software and AQUOS BOARD are registered trademarks or trademarks of Sharp Corporation and/or its affiliated entities. Microsoft and PowerPoint are registered trademarks of Microsoft, Inc. in the United States and/or other countries. Blackboard is a registered trademark of Blackboard Inc., Proemethean, ActivInspire and ClassFlow are registered trademarks or trademarks of Promethean Limied. Google is a registered trademark of Google Inc. Splashtop inc. All other trademarks are the property of their respective owners.

# **SHARP**<sub>8</sub>

## Make Learning and Teaching More Engaging

With a powerful and affordable solution for interactive classrooms



## **Built to Enhance Communication and Collaboration**

Looking for a powerful, yet affordable solution to make your classrooms interactive? The TAA compliant 70" Class (69.5" diagonal) Sharp 4T-B70CT1U AQUOS BOARD<sup>®</sup> interactive display, provides all the essentials for collaborative learning at an affordable price.

Plug-and-play compatibility allows for quick integration with various cloud-based platforms, including Google Classroom, allowing presentations on a large-format display inside the classroom. Additionally, precise 20-point multi-touch functionality allows multiple people to collaborate effectively and creatively to facilitate effective learning. A powerful RS-232C and LAN command set enables flexible remote control from connected devices. Plus, selecting "Public Mode" prevents unwanted operation by people in a classroom or any other public location.

### Just some of the many features include:

• **Simultaneous Writing:** The display lets multiple people write on the screen at the same time using touch pens or fingers, allowing students to take an active part in classroom interactions.

• **Multi OS Support/Plug-and-Play:** Compatible with major operating systems. Your computer automatically recognizes the display when connected, without a complicated driver to install.

• **4K Ultra-HD resolution:** The 4T-B70CT1U interactive display supports 4K Ultra-HD and captures fine textures of still and video images, while also reproducing precise details of small text and complex graphics.

• **Professional Command Control:** RS-232C and LAN command set enables flexible and centralized remote control from connected devices.

• **Protective Glass:** Anti-reflective tempered protective glass increases durability and clarity while protecting the display.

### System Requirements

### Connected Equipment

Hardware	Must have USB 2.0 compliant port
Operating System	Windows® 8.1 (32-bit or 64-bit versions), Windows 10 (32-bit or 64-bit versions) Google Chrome™ OS Version 74 or later macOS® v 10.13, v 10.14, v 10.15

### Supplied Software (Windows)

СРИ	Intel® Core™ i5-6360U or faster Intel® Core™ i7-6650U or faster recommended
Memory	At least 4 GB
Free space on hard drive	At least 4 GB (free space separately required for data storage)


To use the touch panel, connect the bundled USB cable to the computer. The touch panel operates with the standard driver of each OS. On the Mac<sup>®</sup>, operation is only possible in single-touch mode.

### Specifications


Model Name		4T-B70CTIU	
Installation		Landscape	
LCD Panel		70" class (69.5" diagonal) LCD	
	Max. Resolution	3,840 x 2,160 pixels	
	Max. Display Colors (approx.)	1.07 billion colors	
	Pixel Pitch (H × V)	0.40075x 0.40075 mm	
	Contrast Ratio	4,000: 1	
	Viewing Angle (H/V)	176°/176° (CR 10)	
	Active Screen Area (W × H)	60 <sup>5</sup> /s" x 34 <sup>3</sup> /16"	
	Response Time	8.5 ms	
	Backlight	LED, Direct	
Touchscreen	Touch Technology	IR (infrared blocking detection method)	
	PC Connection Port *1	USB Type C x 1	
	Multi Touch	20 points	
	Protection Glass	Thickness: Approx. 4.0mm Shock resistance: 130 cm	
Touch Pen	Passive Pen	2 included	
Computer Input	Video	HDMI	
	Plug & Play	VESA DDC2B	
Video Color System		NTSC-M/PAL-N/PAL-M	
Analog/Digital Tuner		NTSC/ATSC	
Input Terminals*2		HDMI x 2, Analog AV (3.5 mm-diameter mini stereo jack) x 1, ANT/Cable x 1, USB x 1	
Control Terminals*2		Ethernet RJ-45 x 1, RS-232C (3.5 mm-diameter mini stereo jack) x 1	
Output Terminals*2		Audio ( 3.5 mm-diameter mini stereo jack (L/R)) x 1	
Speaker Output		10 W + 10 W	
Power Supply*3		110 V AC, 60 Hz	
Power Consumption		200W	
Operating Temperature*4		0°C to 40°C	
Dimensions (W x D x H) (approx.) (display only)		62 <sup>3</sup> / <sub>4</sub> " x 3 <sup>5</sup> / <sub>16</sub> " x 36 <sup>-13</sup> / <sub>16</sub> "	
Weight (approx.) (display o	only)	100 lbs	

\*1 Use supplied USB cable and adapter to connect with computers \*2 Use a commercially available connection cable for PC and other video connections. \*3 The AC power cord is an inlet type. The cable is bundled (3 pins). \*4 Temperature conditions may change when using the monitor together with optional equipment. In such cases, please check the temperature conditions specified by the optional equipment.

### Dimensions







Units: inch (mm) \*Screen dimensions



SHARP ELECTRONICS CORPORATION 100 Paragon Drive, Montvale, NJ 07645 1-800-BE-SHARP • www.sharpusa.com



are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of MDMI Licensing Administrator, Inc. Manufactured under license from Dolby Laboratories. Dolby and the double-D symbol are trademarks of Dolby Laboratories. Windows is a registered trademark or trademarks of Microsoft Corporation in the US and/or other countries. Google Chrome and Android are trademarks of Google LLC. Max and macOS are trademarks of Apple Inc., registered in the US and other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners. All screen images appearing in this brochure are simulated. Design and specifications are subject to change without prior notice.